




TECNOFLUID

ENGINEERING



SHORT-STROKE CYLINDERS

The short-stroke cylinders of the CC series complete the wide range of special cylinders manufactured by our company for a variety of industrial sectors.

The CC short-stroke hydraulic cylinders can meet the need for small-sized presses.

The main feature of these cylinders is their reduced overall dimensions, compared with ISO cylinders, and therefore can be used to lock or move in very small spaces.

They are manufactured in the double-acting version, with magnetic sensors. Their body is provided with holes for sensors.

All CC short-stroke cylinders are equipped with a magnetic piston with two PTFE anti-friction shoes for a precise guide and reduced friction.

Cylinders can be clamped by means of the holes available on their body.

The CC short-stroke hydraulic cylinders by Tecnofluid meet the strictest reliability requirements, also under heavy duty, whenever precise pushes and considerable work loads are required.

Technical characteristics:

Bore: 20÷50mm

Standard stroke: 20 and 50 mm

Rated pressure: 160 bar


Maximum pressure: 250 bar

Fluid temperature: **-20 ÷ +80°C** (standard gaskets)


Fluid temperature: **-20 ÷ +150°C** (Viton gaskets)

Recommended fluid: Mineral Hydraulic oil / phosphoric esters

Coding key:




STRUCTURAL CHARACTERISTICS



Rif.	Componenti	Materiale	Rif.	Componenti	Materiale
1	Dust scraper	Nitrile rubber + PTFE	8	Guide bushing	Bronze
2	Stem gasket	NBR/fiber	9	O-ring	Nitrile rubber
3	Guiding sliding block	PTFE	10	O-ring	Nitrile rubber
4	Stem	Chromium-plated steel	11	Piston gasket	Nitrile rubber + PTFE
5	Piston	Steel	12	Magnet	Neodymium
6	Guiding sliding block	PTFE	13	semipistone posteriore	Steel
7	Body	Special light alloy	14	Grano antisvitamento	Acciaio brunito


STANDARD VERSION




Piston	20		25		32		40		50		63		80		100	
Stem	14		18		22		22		28		28		36		45	
Stroke	20	50	20	50	20	50	20	50	20	50	20	50	20	50	20	50
A	74	104	77	107	80	110	93	123	95	125	105	135	120	150	130	160
B	60		65		75		85		100		115		140		170	
C	40		45		55		63		75		90		110		140	
CH	11		14		18		18		24		24		32		41	
D	45		50		55		63		76		90		110		135	
E	25		30		35		40		45		55		75		95	
F	27		30		34		34		42		50		60		72	
G	5		6,5		8		7		8		7		7		8	
H	12		14		15		17		20		20		20		25	
I	1/4" G.		1/4" G.		1/4" G.		1/4" G.		1/4" G.		3/8" G.		1/2" G.		1/2" G.	
L	42	72	43	73	46	76	55	85	55,5	85,5	55	85	60	90	65	95
M	20		22		22		24		25		29		35		37	
N	M8		M10		M12		M14		M20		M20		M27		M33	
O	28		32		34		37		37,5		47,5		50		60	
P	10		10		12		12		15		15		20		20	
Q	6,5		8,5		10,5		10,5		13		13		17		17	
R	2		2		3		3		5		5		5		5	
S	33		37		40		43		45		55		60		70	
T		40		40		40		45		45		40		40		30
U	16		21		21		28		33		34		38		45	

OIL FEED VARIANTS (WITHOUT FITTING)


FRONT FEED (NO FIXING HOLES FORESEEN ON THE SHAFT AXIS)



BACK FEED (NO FIXING HOLES FORESEEN ON THE SHAFT AXIS)




LOWER SUPPORT FEED




Piston	20		25		32		40		50		63		80		100	
Stroke	20	50	20	50	20	50	20	50	20	50	20	50	20	50	20	50
U	21		25,5		30		32,5		40		48		59		70	
X	20		22		22		24		25		29		35		37	
Y	42	72	43	73	46	76	55	85	55,5	85,5	55	85	60	90	65	95
Z	4		4		4		4		7		7		7		7	
OR	OR 106		OR 106		OR 106		OR 106		OR 108		OR 108		OR 108		OR 108	

STEM ACCESSORIES

Male terminal EM




Hammer head ET




Type		ES	L	N	S	T	U	V	W g9	Z
EM-20	ET-20	17	15	M8	M8 x 1	12	6	7	16	10
EM-25	ET-25	17	20	M10	M10 x 1,25	14	6	7	16	10
EM-32	ET-32	19	20	M12	M12 x 1,25	16	7	8	18	11
EM-40	ET-40	22	25	M14	M14 x 1,5	18	8	8	18	11
EM-50	ET-50	30	30	M20	M20 x 1,5	28	9	10	22	14
EM-63	ET-63	30	30	M20	M20 x 1,5	28	9	10	22	14
EM-80	ET-80	36	40	M27	M27 x 2	36	12	12,5	28	18
EM-100	ET-100	46	50	M33	M33 x 2	45	14	16	35	22

MAGNETIC SENSORS



Circuit type



TECHNICAL CHARACTERISTICS	
Voltage	1..130 V AC/DC
Max. current	500 mA
Protection degree	IP 67 (DIN 40050)
Cable	2 x 0.25 mm ²
Length	2000 mm
Contact	N.O.